

# LOAD RUNNER

## Solid Waste Transport Trailers **X**SERIES

REAR LOADING TRAILERS

*Increase profits, reduce hauling expenses*



Direct load, no need for an expensive facility

*Rear load directly into the X-Series Trailer from route collection trucks... X-pand your hauling opportunities. A new, innovative and effective approach to transporting solid waste in hard to service areas..*

*Load Runner X-Series is clean, quick and environmentally safe.*



*The Truck-Trailer Mobile Transport System*







# LOAD RUNNER X-SERIES

Solid Waste Transport Trailers  
REAR LOADING TRAILERS

No obstructions in rear of X-Series trailer. This allows for quick and easy loading, sidewalls open and close hydraulically.

With the fact that transfer stations are difficult to site and expensive to construct, and with landfills not being as local and convenient as they used to be, the costs of hauling solid waste direct with route collection trucks has become very expensive and inefficient. As a result, Wilkens Industries has developed an inexpensive method for the transport of solid waste in rural - remote areas, as well as, inner cities. Wilkens Industries would like to introduce you to the **Load Runner X-Series Model** of transport trailers.



## Standard Specifications

### OUTSIDE DIMENSIONS

A	Length	50'
B	Height	13'6"
C	Width Front	102"
D	Width Rear	102"

### CAPACITY

127 CU. YD

### INSIDE DIMENSIONS

E	Length	49'9"
F	Height Front	104"
G	Height Rear	104"
H	Width Front	96"
I	Width Rear	96"

### Trailer Features

J	Sidewall	Front 2/3 .125 Aluminum sheet-post, bi-fold rear section 14GA. steel
K	Top Rail	Aluminum extruded tube 4x6x3/8" 6061 T-6
L	Spreader Bar	3"x3" x1/4" steel tube
M	Bottom Rail	7GA. formed
N	King Pin/Last Axle	41'
O	King Pin Setting	36" with 5/16" steel T-1plate
P	Sub Frame	W12 x 30# I-Beam
Q	Landing Gear	Holland Mark V, cushion skid foot
R	Gear Support	7 GA
S	Gear Braces	3" channel
T	Suspension	Tandem H 9700 Spring
U	Axles & Brakes	(2) 5" Round 25,000# axles, 4S2M ABS with top mount chambers
V	Hubs	10 Bolt unimount
W	Rims	Aluminum disc 8.25x22.5
X	Tires	11R X 22.5, 14Ply
Y	Rear Door	Special steel double door with ratchet latch
Z	Front Panels	125 aluminum sheet & post
King Pin Section		Fabricated from 1/2" T-1 plate
Crossmembers		4"x3.2# on 12" centers, steel I-beam
Light System		Truck light 40 series, lights in bumper
Cover		Front 2/3 roll tarp, rear 15' special manual flip top
Unloading system		Keith Running Floor II
Floor thickness		7/32", #2190 Keith flooring
Landfill Equipment		Tow hooks, push bumpers, catwalk, ladder, in-line pressure filter
Metal Preparation		Exterior sandblasted, epoxy primer
Paint		Gray enamel
Front Corners		10" Diagonal Radius
Weight		19,900#

